

A10P1

Plug-in

8~12W

Country of Origin : Taiwan

Operating Temperature : 0 ~ 40° C

Dimension : 60 x 45 x 30 mm

Approvals / Marks : UL, c-UL, TÜV, CE, CB, PSE

**Features:****Wall-mount Adapter with Exchangeable Plug**

Universal full range Input 100 ~ 240VAC / 47 ~ 63Hz

Output connector: standard: 5.5 x 2.1 x 9.5mm or customer requirement

Overload, over voltage & short circuit protection

1 year warranty

Specification:

		OUTPUT					
OUTPUT	MODEL	Voltage	max. Load	Tolerance	Ripple & Noise	Efficiency	Max. Power
	A10P1-33MP	3.3V	2.5A	± 5%	50mV	min. 60%	8.25W
	A10P1-05MP	5V	2A	± 5%	65mV	min. 60%	10W
	A10P1-06MP	6V	2A	± 5%	70mV	min. 60%	12W
	A10P1-09MP	9V	1.2A	± 5%	90mV	min. 60%	10.8W
	A10P1-12MP	12V	1A	± 5%	120mV	min. 60%	12W
INPUT	Voltage	Universal input 100 ~ 240VAC ±10% full range					
	Frequency	47 ~ 63 Hz					
	Current	0.3A max.					
	Inrush Current	60A@230VAC / 30A@115VAC cold start					
	Leakage Current	< 0.25mA					
PROTECTION	Overload	-					
	Over Voltage	115 ~ 125% auto recovery, when fault has been corrected					
	Over Temp.	-					
	Short Circuit	auto recovery, when fault has been corrected					
OTHERS	Holdup time	16ms after loss of nominal AC input under full load condition					
	Withstand Voltage	HI-POT: I/P-O/P: 5100DC / 10mA / 2 seconds					
	Power Saving	< 1W @ 240VAC (Input wattage by DC output no-load condition)					
Environment	Temperature	Operating: 0 ~ 40°C / Storage: -20 ~ 85°C					
	Humidity	Operating: 20 ~ 90% RH / Storage: 20 ~ 90% RH					
Connection	Input	Plugs: EU, UK, US and AUS (exchangeable)					
	Output	Plug: standard: 5.5 x 2.1 x 9.5 mm, UL1185#18 or customer requirement Cable: standard: 150cm (5ft.)					
SAFETY	Approved:	UL60950 3rd edition / TÜV EN60950:1992 +A1+A2+A3+A4+A11 / CSA22.2No.950					
EMC	EMI	EN55022:1998 / CISPER22 / FCC rules part 15 subpart B / EN61000-3-2,4					
	EMS	EN55024 / EN61000-4-2,3,4,5,6,8,11					
WEIGHT		N.W.: 0.12 kg					