

A15P2

Plug-in

15W

Country of Origin : Taiwan

Operating Temperature : 0 ~ 40° C

Dimension : 68 x 52 x 33 mm

Approvals / Marks : UL, c-UL, TÜV, CE, CB, PSE



Features:

Wall-mount Adapter with Exchangeable Plug

Universal full range Input 100 ~ 240VAC / 47 ~ 63Hz

Output connector: standard: 5.5 x 2.1 x 9.5mm or customer requirement

Overload, over voltage & short circuit protection

1 year warranty

Specification:

		OUTPUT						
OUTPUT	MODEL	Voltage	max. Load	Tolerance	Ripple & Noise	Efficiency	Max. Power	
		A15P2-05MP	5V	3A	± 5%	65mV	min. 70%	15W
		A15P2-12MP	12V	1.3A	± 5%	120mV	min. 70%	15.6W
INPUT	Voltage	Universal input 100 ~ 240VAC ±10% full range						
	Frequency	47 ~ 63 Hz						
	Current	0.5A max.						
	Inrush Current	60A@230VAC / 30A@115VAC cold start						
	Leakage Current	< 0.25mA						
PROTECTION	Overload	-						
	Over Voltage	115 ~ 125% auto recovery, when fault has been corrected						
	Over Temp.	-						
	Short Circuit	auto recovery, when fault has been corrected						
OTHERS	Holdup time	8ms after loss of nominal AC input under full load condition						
	Withstand Voltage	HI-POT: I/P-O/P: 5100DC / 10mA / 2 seconds						
	Power Saving	< 1W @ 240VAC (Input wattage by DC output no-load condition)						
Environment	Temperature	Operating: 0 ~ 40°C / Storage: -20 ~ 85°C						
	Humidity	Operating: 20 ~ 90% RH / Storage: 20 ~ 90% RH						
Connection	Input	Plugs: EU, UK, US and AUS (exchangeable)						
	Output	Plug: standard: 5.5 x 2.1 x 9.5 mm, UL1185#18 or customer requirement Cable: standard: 150cm (5ft.)						
SAFETY	Approved:	UL60950 3rd edition 2000 / TÜV EN60950:2000 / CAN/CSA 22.2 No.60950-00 3rd edition 2000 / PSE						
EMC	EMI	EN55022 CISPER22 Class B						
	EMS	EN55024						
WEIGHT		N.W.: 0.14 kg						