

Country of Origin : China  
 Operating Temperature : 0 ~ 40° C  
 Dimension : 76 x 45 x 28 mm  
 Approvals / Marks : UL, c-UL, TÜV, CB, CE, BSMI

**Features:**

Desktop Type with IEC320-C8 inlet  
 No Load Standby Power : 0.6W max.  
 High efficiency design & attractive appearance  
 Over voltage, overload & short circuit protection  
 High Performance  
 1 year warranty

**Specification:**

		OUTPUT				
	MODEL	Voltage	Load	Tolerance	Ripple & Noise (max)	Max. Output Power
	ACSD-11	5V	3.5A	±5%	150mV	17.5W
	ACSD-12	6V	3.3A	±5%	150mV	19.8W
	ACSD-13	7.5V	3A	±5%	150mV	22.5W
	ACSD-14	9V	2.6A	±5%	150mV	23.4W
	ACSD-15	12V	2A	±5%	150mV	24W
	ACSD-16	15V	1.66A	±5%	150mV	24.9W
	ACSD-17	18V	1.4A	±5%	150mV	25.2W
	ACSD-30	24V	0.55A	±5%	100mV	13.2W
	ACSD-31	5V	2A	±5%	70mV	10W
INPUT	Voltage	90 ~ 264VAC				
	Frequency	47 ~ 63 Hz				
	Current	0.7Amax				
	Inrush Current	20A @ 115VAC / 40A @ 230VAC				
	Leakage Current	< 0.25mA @ 264VAC				
PROTECTION	Overload	Yes				
	Over Voltage	Yes				
	Over Temp.	-				
	Short Circuit	Yes				
OTHERS	Holdup time	12ms at full load and 115VAC				
Environment	Temperature	Operating: 0 ~ 40°C / Derating: 40 ~ 50°C : 2%/°C / Storage: -40 ~ 85°C				
	Humidity	20% ~ 90% RH				
Connection	Input	IEC320-C8				
	Output	Plug: standard: 5.5 x 2.1 x 9.5 mm or customer requirement / Cable: 120 cm (typical) or requirement				
M.T.B.F.		> 50K hours				
SAFETY		Approved: UL1950 / c-UL / TÜV EN60950 / CB / BSMI				
EMC	EMI	meets: EN55022 / FCC Part 15 Class B / CISPER22 Class B				
	EMS	meets: EN55024				
WEIGHT		N.W.: 0.2 kg				