



Country of Origin : China  
 Operating Temperature : 0 ~ 40° C  
 Dimension : 55 x 42 x 28 mm  
 Approvals / Marks : UL, c-UL, TÜV, CE, CB, PSE

### Features:

Available as EU, UK, US or AUS model

Wide range 90~264VAC / 47~63Hz

Output connector: standard: 5.5 x 2.1 x 9.5mm or customer requirement

Attractive Appearance / Light Weight / High Performance

Overload, Over Voltage & Short Circuit protection

1 year warranty

### Specification:

		OUTPUT						
	MODEL	Voltage	min. Load	max. Load	Tolerance	Ripple & N.	Efficiency	Max. Power
OUTPUT	ACTN-01	5V	0A	1.3A	±5%	80mV	70% min.	6.5W
	ACTN-02	6V	0A	1.1A	±5%	80mV	70% min.	6.6W
	ACTN-03	6.5V	0A	1.02A	±5%	80mV	70% min.	6.6W
	ACTN-04	7.5V	0A	0.9A	±5%	80mV	70% min.	6.75W
	ACTN-05	9V	0A	0.8A	±5%	80mV	70% min.	7.2W
	ACTN-06	12V	0A	0.62A	±5%	80mV	70% min.	7.4W
	ACTN-07	15V	0A	0.5A	±5%	80mV	70% min.	7.5W
<hr/>								
INPUT	Voltage	90 ~ 264VAC						
	Frequency	47 ~ 63Hz						
	Current	0.3A max.						
	Inrush Current (max)	40A @ 230VAC / 20A @ 115VAC						
PROTECTION	Overload	Yes, Pulsing mode, auto recovery						
	Over Voltage	Yes						
	Short Circuit	Yes						
OTHERS	Startup time	30ms @ 115VAC and full load						
	Holdup time	12ms @ 115VAC and full load						
	Cooling	Free air convection						
	Withstand Voltage	I/P-O/P: 3KVAC / 3 seconds						
	Power Consumption	No Load: 0.3W @ 264VAC						
Environment	Temperature	Operating: 0 ~ 40°C / Storage: -40 ~ 85°C						
	Humidity	Operating: 20% ~ 90% RH						
Connection	Input	Plug: standard: European-plug / UK-plug, US-plug or AUS-plug on request						
	Output	Plug: standard: 5.5 x 2.1 x 9.5 mm or customer requirement / Cable: standard: 180cm (6ft.)						
MTBF	> 50K hours							
SAFETY	UL1950 / TÜV EN60905 / CE / CB / CSA 22.2 / T-Mark							
EMC	EMI	FCC Class B / CISPR22 Class B / EN61000-3-2,3						
	EMS	EN55024						
WEIGHT	N.W.: 0.1 kg							