

Features

- Compliant to DoE 2016 (Level VI)
- ErP Stage 2, NRCan & GEMS Level VI
- No Load Power Consumption < 0.1 W
- Regulated Output with Low Ripple Noise
- 1 Year Warranty



Marks / Approvals



Specifications

Product similar to photo, variations possible.

	MODEL	Voltage	Min. Load	Max. Load	Max. Power
	STD 12090	12 V	0.0 A	9.0 A	108 W
	STD 15080	15 V	0.0 A	5.0 A	120 W
	STD 16075	16 V	0.0 A	7.5 A	120 W
	STD 18066	18 V	0.0 A	6.6 A	120 W
	STD 19063	19 V	0.0 A	6.3 A	120 W
	STD 20060	20 V	0.0 A	6.0 A	120 W
	STD 24050	24 V	0.0 A	5.0 A	120 W
	STD 30040	30 V	0.0 A	4.0 A	120 W
	STD 48025	48 V	0.0 A	2.5 A	120 W
	STD 56021	56 V	0.0 A	2.15 A	120 W
INPUT	Voltage	AC 100 V – 240 V			
	Frequency	50 Hz - 60 Hz			
	Current	1.6 A max.			
	Protection	Internal Primary Current Fuse, Inrush Limiting			
OUTPUT	Load Regulation	± 5 % (typical)			
	Ripple	1 % – 2 % V p-p max. for output voltage at full load			
	Transient Response	0.5 ms for 50 % load change typical			
	Leakage Current	0.25 mA max.			
	Protection	Short circuit Protection • Over Voltage Protection • Over Current Protection			
OTHERS	Cooling	Convection			
	Efficiency	DoE Level VI • Energy Star • ErP Stage 2 • NRCan & GEMS Level VI Certified			
	Holdup Time	10 ms at full load			
	Dielectric Withstand	AC 3000 V Primary – Secondary			
	MTBF	300,000 calculated hours at 25 °C by telcordia SR-332			
ENVIRONMENT	Temperature	Operating: 0 °C – 40 °C / Storage: -20 °C – 80 °C			
	Humidity	Operating: 20 % RH – 80 % RH / Storage: 10 % RH – 90 % RH			
EMI Conduction & Radiation	Compliance to EN 55022 Class B				
Harmonic Current	Compliance to EN 61000-3-2, -3				
EMS Immunity	Compliance to IEC 61000-1-2, -3, -4, -5, -6, -8, -11				
Safety	IEC / EN / UL 60950-1 • CE • RCM • PSE • BSMI				
Case Dimensions	168 mm × 66 mm × 39 mm				

Specifications subject to change without notice