

Features

- Compliance to Lighting and LED Equipment Regulations
- IP20 for Indoor Installation
- MM Marking for Furniture Installation
- Suitable for LED Lighting Applications
- 1 Year Warranty

Marks / Approvals



Specifications

Image similar, variations possible

MODEL No.	Voltage	Min. Load	Max. Load	Max. Power	Ripple & Noise
SE30-12VL	12 V	0.00 A	2.5 A	30 W	240 mV p-p
SE30-24VL	24 V	0.00 A	1.25 A	30 W	240 mV p-p
INPUT	Voltage	AC 180 V – 264 V			
	Frequency	50 Hz - 60 Hz			
	Current (rms max)	< 0.25 A			
	Power Factor	≥ 0.9			
PROTECTION	Overload	Yes, Auto Recovery			
	Overvoltage	Yes, Latch Off			
	Short Circuit	Yes, Auto Recovery			
	Over Temperature	Yes, temperature exceeding max. value at detection point, restart after cut-off (latch-off)			
	Input Surge Current	< 60 A peak			
OTHERS	Cooling	Convection Cooling			
	Efficiency	≥ 85 % typical			
	Startup Time	< 0.5 s, at 25 °C rated input voltage, output max. rated power			
	Protection Marking	IP20 (IEC 60529)			
	Working Noise	< 35 dB, pickup at 10 cm			
	Protection Class	Class II			
	Case Material	Plastic cover with terminal block H03VVH2-F 2x0.75mm²			
Environment	Temperature	Operating: -20 °C to 45 °C / Max. Case Temperature: 80 °C			
	Humidity	Operating: 45 % RH to 85 % RH			
Lifetime	30 000 hrs at max. Ta, rated input voltage, output max. rated power				
SAFETY	IEC / EN 61347-1, IEC / EN 61347-2-13				
EMI	EN 55015				
EMS	EN 61547; EN 61000-4-2, -3, -4, -5, -6				
Harmonic	EN 61000-3-2 Class C				
Case Dimensions	149 mm × 40.4 mm × 26.7 mm				

