

Features:



- Universal AC input / Full range
- Built in active PFC function, PF > 0.90
- Green design, No-load power consumption < 0.7W
- Protection: Short circuit, Over load, Over voltage
Brown-out (Low AC Input Voltage)
- High operation temperature up to 70°C
- Withstand 2G vibration test
- 3 years warranty



MODEL		AK-200-05	AK-200-7.5	AK-200-12	AK-200-13.5	AK-200-15	AK-200-24	AK-200-27	AK-200-48
Output	DC Voltage Range	5V	7.5V	12V	13.5V	15V	24V	27V	48V
	Rated Current	32A	26.7A	16.7A	14.9A	13.4A	8.4A	7.5A	4.2A
	Current Range	0 ~ 32A	0 ~ 26.7A	0 ~ 16.7A	0 ~ 14.9A	0 ~ 13.4A	0 ~ 8.4A	0 ~ 7.5A	0 ~ 4.2A
	Rated Power	160W	200W	200W	201W	201W	201W	202W	201W
	Ripple & Noise (Max.) Note.2	100mVp-p	100mVp-p	100mVp-p	100mVp-p	100mVp-p	120mVp-p	120mVp-p	200mVp-p
	Voltage Adj. Range	4.5~5.5V	6.75~8.25V	10.8~13.2V	12.15~14.85V	13.5~16.5V	21.6~26.4V	24.3~29.7V	43.2~52.8V
	Voltage Tolerance Note.3	±2%	±1.5%	±1%	±1%	±1%	±1%	±1%	±1%
	Line Regulation	±1%	±1%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	Load Regulation	±1%	±1%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	Setup, Rise Time	< 2500ms, < 110ms at full load							
Hold Up Time (Typ.)	> 32ms / 230VAC, > 10ms / 115VAC at full load								
Input	Voltage Range Note.4	90 ~ 264VAC, 127 ~ 370VDC							
	Frequency Range	50 / 60Hz							
	Power Factor (Typ.)	> 0.92 / 230VAC, > 0.98 / 115VAC at full load							
	Efficiency (Typ.)	78%	81%	85%	86%	86%	87%	88%	88%
	AC Current (Typ.)	2.3A / 115VAC, 1.2A / 230VAC							
	Inrush Current (Typ.)	30A / 115VAC, 55A / 230VAC							
	Leakage Current	< 2mA / 230VAC							
Protection	Over Load	> 105% rated output power Protection type: Hiccup mode							
	Over Voltage	115 ~ 150% rated output voltage Protection type: latch-off mode							
	Over Temperature	90 ±5°C detect on NTC Protection type: shut down o/p voltage, after temperature goes down and re-power ON to recover							
	Working Temp.	-20 ~ +70°C (Refer to de-rating curve)							
	Working Humidity	20 ~ 90% RH non-condensing							
Environment	Storage Temp. & Humidity	-40 ~ +85°C, 10 ~ 95% RH							
	Temp. Coefficient	±0.03% / °C (0 ~ 50°C)							
	Vibration	10 ~ 500Hz, 2G 10min. / 1cycle, period for 60min. Each along X, Y, Z axes							
	Safety & EMC	Safety Standards	Certified UL 60950-1; EN 60950-1						
Withstand Voltage Note.6		I/P-O/P: 3KVAC (4242VDC), I/P-FG: 1.5KVAC (2121VDC), O/P-FG: 0.5KVAC (707VDC), 1min							
Isolation Resistance		I/P-O/P, I/P-FG, O/P-FG: 100M Ohms / 500VDC							
EMI Conduction & Radiation		Certified EN 55022							
Harmonic Current		Certified EN 61000-3-2; EN 61000-3-3							
EMS Immunity Note.5		Certified EN 61204-3; EN 55024; IEC 61000-4-2, 3, 4, 5, 6, 8, 11							
Others	MTBF	327.7K HRS Certified MIL-HDBK-217F							
	Cooling	Fan							
	Dimension (WxHxD)	98x42x197 mm / 3.858x1.654x7.756 inch							
	Packing	0.86kg; 24pcs / 20.64kg / 1.29CUFT							
Note	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor. 3. Tolerance: includes setup time tolerance, line regulation and load regulation. 4. De-rating may apply in low input voltage. Please check the de-rating curve for more details. 5. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives. 6. This test is done without enclosure.								


Mechanical Drawings:

Unit : mm



De-rating Curve:

Load VS. Temp.



Load VS. I/P Voltage

Ta=25°C

